Linesque

























Application: • Roller, Roman & Panel Window Blinds

· Wide Width Windows

Characteristics: • 3000mm

Technical: • Composition: 100% Polyester with Acrylic Coating

• PVC Free | Lead Free

• Light Fastness: 6 (Blue Scale) Tested to ISO 105-B02:2014

• Nominal Weight: BO 431gsm | LF 285gsm

• Nominal Thickness: BO 0.65mm | LF 0.55mm

Performance: • Opacity: 100% Blackout

• Tear Resistance:

LF Mean Length 126 Warp 128 N BO Mean Length 150 Warp 139 N Tested to AS 2001.2.10-1986

Protection: • Complies with Building Code of Australia requirements for Class 2 to 9 (a) buildings.

Tested to AS 1530 Part III.

Air Quality: VOC Tested US EPA 5021A:2003

• Greenquard Gold - accredited for use in sensitive areas eg schools and healthcare facilities (tested against California Section 01359 for low chemical emissions (VOCs))

Care: • Surface dust should be removed with duster or soft cloth. Never use abrasive products or solvent/industrial based cleaners.

Note: • Colour variances may occur between fabric production batches. These variances are within industry tolerances.

Colour Range *





fig



dove



fleece





raffia

fossil aspen



denim



* Images representative only

Light Filtering Colours



Quality	SHAW Colour Name	Quality	SHAW Colour Name
Blackout (BO)	Blanco	Light Filtering (LF)	Lily
Blackout (BO)	Almond	Light Filtering (LF)	Oatcake
Blackout (BO)	Soba	Light Filtering (LF)	Wicker
Blackout (BO)	Raffia	Light Filtering (LF)	Hazel
Blackout (BO)	Vine	Light Filtering (LF)	Trellis
Blackout (BO)	Fig	Light Filtering (LF)	Chestnut
Blackout (BO)	Dove	Light Filtering (LF)	Owl
Blackout (BO)	Fleece	Light Filtering (LF)	Winter
Blackout (BO)	Aspen	Light Filtering (LF)	Delta
Blackout (BO)	Fossil	Light Filtering (LF)	Granite
Blackout (BO)	Breeze	Light Filtering (LF)	Stonewash
Blackout (BO)	Denim	Light Filtering (LF)	Levi

LF and BO colour variation occurs due to the nature of the finishing process.

